




The Husqvarna 130BT is a unique lightweight commercial back pack blower in a class of its own. It combines very low weight and ease of use with impressive performance. Features include a new X-Torq® engine with E-TECH® II emission control and a harness and controls that are ergonomically designed for high capacity and ease of use.




HIGH BLOWING CAPACITY

The powerful and easy to start X-Torq® engine in combination with effective fan design delivers high air speed and high air flow.



ERGONOMIC HANDLE

The handle can be angled and has rubber inserts for a stable, comfortable grip.



COMFORTABLE HARNESS

Comfortable padded harness.



X-TORQ® ENGINE

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.

Features

- Fuel pump for easy starting
- Adjustable handle increased comfort
- Air speed cruise control

Technical data

| | |
|---|---------------------------------------|
| Cylinder displacement | 29.5 cm ³ / 1.8 cu.inch |
| Power output | 0.96 kW |
| Maximum power speed | 8000 rpm |
| Carburettor | Rotary valve |
| Fuel tank volume | 0.9 lit / 30.43 fl oz |
| Fuel consumption | 392 g/kWh |
| Idling speed | 3000 rpm |
| Spark plug | NGK CMR7H |
| Air flow in housing | 12.2 m ³ /min / 430.84 cfm |
| Air flow in pipe | 10.2 m ³ /min / 360.21 cfm |
| Air speed | 64.82 m/s / 145 mph |
| Equivalent vibration level (ahv, eq) handle | 2.5 m/s ² |
| Sound pressure level at operators ear | 94 dB(A) |
| Sound power level, guaranteed (LWA) | 102 dB(A) |
| OEM Harness | Integrated |
| OEM Nozzle type | Round |
| Weight | 6.7 kg / 14.77 lbs |

