



Husqvarna 143R-II is a rugged brushcutter designed for tough use. The handle bar has an asymmetrical design which leads to better working position. Delivered with double harness.



STANDARD DOUBLE HARNESS
Standard harness for lighter brushcutters.



FUEL PUMP
Fuel pump designed for easy starting.



COMBI-GUARD
The cutting attachment combi-guard can be used with either a grass blade or a trimmer head.



ROBUST HANDLE SYSTEM
The handle bar is attached to the tube by a die casted clamp for high durability.

Features

- Heavy duty clutch
- Easy to service and maintain starter
- Efficient air filter
- Grass bevel gear for best cutting performance

Technical data

Cylinder displacement	41.5 cm ³ / 2.53 cu.inch
Power output	1.5 kW
Maximum power speed	7500 rpm
Maximum recommended engine speed	10400 rpm
Carburettor	Walbro WYJ
Fuel tank volume	0.95 lit / 32.12 fl oz
Fuel consumption	653 g/kWh
Idling speed	2500 rpm
Spark plug	NGK BPMR7A
Electrode gap	0.6 mm / 0.02 "
Equivalent vibration level (ahv, eq) left / right handle	5.1/6 m/s ²
Sound pressure level at operators ear	94 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)
Gear ratio	1:1.4
Drive gear angle	30 °
OEM Trimmer head	T45XM12
OEM Grass blade	Multi 275-4
OEM Saw blade	–
OEM Harness	Standard double harness
Weight (excl. cutting equipment)	7.6 kg / 16.75 lbs
Tube length	1483 mm / 58.39 inch
Tube diameter	25.4 mm / 1 "

