



Husqvarna 153R is a rugged brushcutter designed for tough use. The handle bar has an asymmetrical design which leads to better working position. Delivered with double harness.



STANDARD DOUBLE HARNESS
Standard harness for lighter brushcutters.



FUEL PUMP
Fuel pump designed for easy starting.



ROBUST HANDLE SYSTEM
The handle bar is attached to the tube by a die casted clamp for high durability.



HEAVY DUTY CLUTCH
The heavy duty clutch facilitates tough work using long cords and large diameter cutting knife.

Features

- Easy to service and maintain starter
- Grass bevel gear for best cutting performance
- Versatile use with combi guard
- Chromium cylinder bore for extended product life
- Comfortable handle design
- Tap 'n Go trimmer head

Technical data

Cylinder displacement	50.2 cm ³ / 3.06 cu.inch
Power output	1.6 kW
Maximum power speed	6500 rpm
Maximum recommended engine speed	10400 rpm
Carburettor	Walbro WYJ
Fuel tank volume	1 lit / 33.81 fl oz
Equivalent vibration level (ahv, eq) left / right handle	4.1/3.5 m/s ²
Sound pressure level at operators ear	95 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Gear ratio	1:1.4
Drive gear angle	35 °
OEM Trimmer head	T45XM12
OEM Grass blade	Multi 275-4
OEM Harness	Standard double harness
Weight (excl. cutting equipment)	7.6 kg / 16.75 lbs

