


Labour-saving hedge trimmer with adjustable cutter blade angle for optimal maneuverability. The engine balances the cutter blade, which can be angled to reach even to the top of bushes. Also equipped with a reduced emission E-TECH® engine and Smart Start® and fuel pump for easier starting.




LOW WEIGHT

The hedge trimmer's low weight and balanced centre of gravity make it easy to manoeuvre in different positions.




ENGINE POSITION

The engine position also helps divert exhaust fumes away from the user.



ADJUSTABLE CUTTER BAR

Adjustable cutting bar for greater versatility and less tiring work.



AUTO RETURN STOP SWITCH

Stop switch automatically resets to the ON position for trouble-free starting.

Features

- Smart Start® for easy starting
- E-TECH® for reduced exhaust emissions
- Comfortable handles
- Fuel pump for easy starting

Technical data

Cylinder displacement	24.5 cm ³ / 1.5 cu.inch
Power output	0.9 kW
Maximum power speed	8400 rpm
Maximum recommended engine speed	12600 rpm
Carburettor	Hualong
Fuel tank volume	0.5 lit / 16.91 fl oz
Fuel consumption	600 g/kWh
Idling speed	2700 rpm
Spark plug	NGK BPMR7A
Electrode gap	0.5 mm / 0.02 "
Air filter type	Foam
Equivalent vibration level (ahv, eq) front / rear handle	4.2/4.2 m/s ²
Sound pressure level at operators ear	94 dB(A)
Sound power level, guaranteed (LWA)	106 dB(A)
Gear ratio	4.78:1
Knife Length	65 cm / 25.6 inch
Knife adjustment range, up/down	25/45°
Teeth opening	29 mm / 1.14 "
Recommended maximum twig diameter	20 mm / 0.79 "
Cutting speed	4184 cut/min
Weight	6.2 kg / 13.67 lbs

