



Pole saw with rapid acceleration and easy starting E-TECH® II engine. The versatile cutter head makes it easy to reach even dense trees and bushes without using a ladder or cherry picker. Low weight, good balance and rear-mounted engine provide a comfortable working position and reduced exhaust fumes. The cutter head has adjustable and automatic chain lubrication.



**BALANCE FLEX**  
 Harness with ergonomic design.  
 Flexible suspension to reduce stress  
 on arms in all working positions.



**CHAIN LUBRICATION**  
 Adjustable, automatic chain  
 lubrication.



**DETACHABLE SHAFT**  
 Detachable shaft for easy transport  
 and storage.



**REAR IMPACT GUARD**  
 The rear-impact guard protects the  
 engine from wear and damage.

## Features

- Auto return stop switch for easy starting
- Smart Start® for easy starting
- Tool less chain tensioner
- Comfortable soft grip handles
- Inertia balancing wheel reduces vibration
- Fuel pump for easy starting

## Technical data

Cylinder displacement	24.5 cm <sup>3</sup> / 1.5 cu.inch
Power output	0.9 kW
Maximum power speed	8400 rpm
Maximum recommended engine speed	12500 rpm
Carburettor	Hualong
Fuel tank volume	0.5 lit / 16.91 fl oz
Fuel consumption	550 g/kWh
Idling speed	2700 rpm
Spark plug	Champion RCJ6Y
Electrode gap	0.5 mm / 0.02 "
Air filter type	Foam
Oil tank volume	0.22 lit / 0.5 US pint
Equivalent vibration level (ahv, eq) front / rear handle	3.4 / 1.9 m/s <sup>2</sup>
Sound pressure level at operators ear	86 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	25-30 cm / 10"- 12"
Weight (excl. cutting equipment)	6.4 kg / 14.11 lbs
Length, extended, including cutting equipment	350 cm / 137.8"

