



Husqvarna 356BTx is a revolutionary new concept for commercial blowers. Top class blowing performance is provided by the well built in E-TECH® II engine, low noise technology, and unique ergonomics. Husqvarna 356BTx is equipped with a tube mounted throttle control.



EFFECTIVE NOISE DAMPENING

Minimal noise with a gentler tone. The engine, fan housing and insulation reduce noise dramatically.



HIGH BLOWING CAPACITY

High blowing capacity.



ERGONOMIC HARNESS

Comfortable, ventilated and load-reducing harness with hip belt and wide shoulder straps.



AIR INJECTION

Unique intake air cleaning for longer operating time.

Features

- LowVib® reduce vibrations
- Comfortable handle design
- Superiour fuel economy and long operating time
- Easy to access engine with snap lock cover
- Centre of gravity close to the user's back, easy to carry
- Fuel pump for easy starting

Technical data

Cylinder displacement	51.7 cm ³ / 3.2 cu.inch
Power output	2.4 kW
Maximum power speed	6000 rpm
Maximum recommended engine speed	6700 rpm
Carburettor	Zama
Fuel tank volume	1.5 lit / 50.72 fl oz
Fuel consumption	400 g/kWh
Idling speed	2300 rpm
Spark plug	NGK BPMR7A
Electrode gap	0.5 mm / 0.02"
Air filter type	Foam
Air flow in housing	21.7 m ³ /min / 766.33 cfm
Air flow in pipe	13.4 m ³ /min / 473.22 cfm
Air speed	79.13 m/s / 177 mph
Equivalent vibration level (ahv, eq) handle	3.9 m/s ²
Sound pressure level at operators ear	91 dB(A)
Sound power level, guaranteed (LWA)	100 dB(A)
OEM Harness	Integrated
OEM Nozzle type	Round+ Flat
Weight	10.4 kg / 22.9 lbs
Tube diameter	60 mm / 2.4"

