




An advanced large-size XP®-saw, developed for the toughest forestry jobs. A perfect saw for hard wood logging with longer bars. This saw has classic Husqvarna XP® -features such as high power to weight ratio, along with a rugged, high-speed engine with an improved cylinder and anti-vibration carburettor. The XP® G model has heated handles. XP®



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



LOWVIB®

Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.



MAGNESIUM CRANKCASE

Sturdily built crankcase withstands high rpms and tough professional use, ensuring a long service life.



THREE-PIECE CRANKSHAFT

Forged three-piece crankshaft for maximum durability for the toughest applications.

Features

- Felling marks for correct felling direction
- Ergonomic grip with angled front handle
- Adjustable chain oil pump
- Quick-release air filter
- Easy to maintain with snap locked filter cover
- Smart Start® for easy starting

Technical data

Cylinder displacement	94 cm ³ / 5.74 cu.inch
Power output	4.9 kW
Maximum power speed	8700 rpm
Maximum recommended engine speed	12500 rpm
Fuel tank volume	0.9 lit / 30.43 fl oz
Fuel consumption	470 g/kWh
Idling speed	2500 rpm
Spark plug	Champion RCJ6Y
Electrode gap	0.5 mm / 0.02 "
Torque, max.	5.9 Nm/6000 rpm
Oil tank volume	0.5 lit / 1.1 US pint
Oil pump type	Automatic
Oil pump capacity	15-20 ml/min
Equivalent vibration level (ahv, eq) front / rear handle	6.5/10.2 m/s ²
Sound pressure level at operators ear	102 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Chain pitch	3/8", .404"
Recommended bar length, min-max	45-90 cm / 18"-36"
Chain speed at max power	20.8 m/s / 68.24 fts
Chain gauge	0.058 "
Weight (excl. cutting equipment)	7.9 kg / 17.4 lbs

