



New powerful all-round saw for people who value professional qualities in a saw. The X-Torq® engine means lower fuel consumption and reduced emission levels. Auto return stop switch, tool-less chain tensioner and visible fuel level makes the saw easier to handle. Equipped with Smart Start® and fuel pump to every time ensure easy starts.



INERTIA CHAIN BRAKE
Effective inertia-activated chain brake.



SMART START®
The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.



AIR INJECTION
Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



X-TORQ®
Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.

Features

- Quick-release air filter
- Ergonomic soft grip rear handle
- Felling marks for correct felling direction
- Intuitive, combined choke/stop control
- Easy to maintain with snap locked cylinder cover
- Maximum durability for tough applications

Technical data

Cylinder displacement	50.2 cm ³ / 3.06 cu.inch
Power output	2.4 kW
Maximum power speed	9000 rpm
Fuel tank volume	0.45 lit / 15.22 fl oz
Fuel consumption	504 g/kWh
Idling speed	2700 rpm
Spark plug	NGK BPMR7A, Champion RCJ7Y
Electrode gap	0.5 mm / 0.02"
Torque, max.	2.6 Nm / 7200 rpm
Oil tank volume	0.26 lit / 0.55 US pint
Oil pump type	Fixed flow
Oil pump capacity	13-13 ml/min
Equivalent vibration level (ahv, eq) front / rear handle	2.3/2.7 m/s ²
Sound pressure level at operators ear	104 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Chain pitch	.325"
Recommended bar length, min-max	33-50 cm / 13"-20"
Chain speed at max power	17.34 m/s / 56.89 fts
Weight (excl. cutting equipment)	5.1 kg / 11.33 lbs

