



Husqvarna 562 XP® is developed for professional loggers and skilled land owners. The saw has a ground breaking design and is loaded with innovative solutions for efficient, convenient operation with large air filter and the ability to fit 28" bars. Our unique X-Torq® engine technology provide more power where you need it, up to 20% less fuel consumption and 75% less exhaust emission. RevBoost™ provide instant high chain speed for extra efficient delimiting.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



AUTOTUNE

AutoTune gives optimal engine performance throughout automatic engine setting. No time spent on carburettor adjustments. It compensates for different fuels, altitude, humidity, temperature and clogged air filter.



REVBOOST™

Rapid acceleration and higher chain speed for best limbing performance.



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.

Features

- LowVib® sparing the user's arms and hands
- Fast acceleration
- Adjustable chain oil pump
- Quick-release air filter
- Intuitive, combined choke/stop control
- Quick and easy chain adjustment

Technical data

Cylinder displacement	59.8 cm ³ / 3.65 cu.inch
Power output	3.5 kW
Maximum power speed	9600 rpm
Maximum recommended engine speed	14000 rpm
Fuel tank volume	0.65 lit / 21.98 fl oz
Fuel consumption	494 g/kWh
Idling speed	2800 rpm
Spark plug	NGK CMR6H
Electrode gap	0.5 mm / 0"
Torque, max.	3.65 Nm / 8100 rpm
Oil tank volume	0.35 lit / 0.7 US pint
Oil pump type	Adjustable flow
Oil pump capacity	6-15 ml/min
Equivalent vibration level (ahv, eq) front / rear handle	4.4/5.3 m/s ²
Sound pressure level at operators ear	106 dB(A)
Sound power level, guaranteed (LWA)	118 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	38-71 cm / 15"-28"
Chain speed at max power	21.3 m/s / 69.9 fts
Weight (excl. cutting equipment)	5.7 kg / 12.57 lbs

