



The Husqvarna PZ Series represents the latest in high performance drive systems and operator interface. Combined with high productivity cutting deck designs, these mowers deliver premium cut quality and clipping dispersal at higher ground speeds. Careful consideration of components and design not only provide extended durability but unprecedented ease of service access. The PZ 29 is delivered deckless and can be fitted with 137 cm/54" and 153 cm/60" fabricated side discharge cutting decks as well as a 155 cm/61" Combi cutting deck (which offers mulching and rear discharge).



ZERO-TURN STEERING SYSTEM

Individual, hydraulic wheel-drive provides very precise manoeuvring and allows the mower to rotate around its own axle, without any turning radius.



FLAT-FREE CASTERS

Durable steel front caster yokes feature heavy-duty tapered roller bearings and flat-free tires.



REMOVABLE FOOT PAN

Removable dimpled-steel foot pan for easy access to deck belt pulleys, spindles and clean-up.



CONVENIENT OPERATOR INTERFACE

The control panel is ergonomic in design and within easy reach of operator.

Features

- Hour meter with service minder
- Vibration-isolated platform for more comfort
- Comfortable full suspension seat
- Increased versatility with triple bag collectors
- Commercial grade engines by Kawasaki/Kohler
- Easy to service hydro drive system

Technical data

Engine manufacturer	Kawasaki
Engine name	FX Series
Power	25.5 hp
Cylinder displacement	852 cm ³ / 52 cu.inch
Cylinders	2
Engine cooling	Air
Air Filter type	Heavy-Duty Canister Style
Fuel Type	Gasoline
Fuel tank volume	41.6 lit / 11 gal.
Fuel tank location	Side (Dual)
Engine lubrication type	Full pressure
Oil capacity	2 lit / 67.2 fl oz
Oil filter	Yes
Transmission type	Pump/Wheel motor
Transmission manufacturer	Hydro-Gear/Parker
Pump displacement	12 cm ³
Wheel motor displacement	311.4 cm ³ / 19 cu.inch
Fan-cooled pumps	Yes
Hydraulic reservoir	5.7 lit / 6 qt
Speed forward, min-max	0-19.3 km/h / 0-12 mph
Speed reverse, min-max	0-9.7 km/h / 0-6 mph
Cutting deck material	Steel
Cutting height, min-max	25 - 127 mm / 1 - 5 inch
Blade engagement	Electric clutch
Clutch rating	339 Nm / 250 ft.lb
Blades	3
Deck lifting system	Manual, foot activated
Powder-coated cutting deck	Yes
ROPS	Yes
Flat-free front tyres	Yes
Seat type	Premium, suspension
Seat material	Vinyl
Seat suspension	Yes
Seat back height	High
Armrests	Yes
Hour meter	Digital with pre-programmed service intervals
Cupholder	Yes
Tyre size, front	13x6.5-6"
Tyre size, rear	23x10.5-12"
Base machine, length	209.5 cm / 82.5 inch
Base machine, height (ROPS down)	120.6 cm / 47.5 inch
Base machine, height (ROPS up)	182.9 cm / 72 inch
Weight	422.3 kg / 931 lbs

