



Powerful and versatile Rider with twin-cylinder engine and optional 94, 103 or 112 cm Combi cutting decks, offering first-class BioClip® and rear ejection cutting. Suitable for landowners who demand superior efficiency, manoeuvrability and perfect results all year round. The articulated steering system and front-mounted cutting deck enables intuitive operation, excellent mowing accessibility and great overview of your working area. In short - this Rider gives you the ultimate driving experience. Can easily be fitted with a number of attachments such as broom, snow blade and snow thrower, for maximum output throughout the year. Features like pedal-operated hydrostatic transmission, easy-access controls, headlights and cutting deck service position, makes operating and servicing this Rider a pleasure.




ARTICULATED STEERING

The unique articulated steering system allows the rear pair of wheels to swing in underneath the machine. The result is superior manoeuvrability with a minimum turning radius at full lock.



FRONT-MOUNTED CUTTING DECK

Front-mounted cutting deck for excellent accessibility into corners and under bushes, park benches etc.



OPTIONAL COMBI CUTTING DECK

This Rider is delivered deckless and can be fitted with 94, 103 or 112 cm Combi cutting decks for efficient BioClip® and rear ejection cutting.



SERVICE POSITION

Service position on the cutting deck facilitates cleaning and service.

Features

- Comfortable driver's position
- Accessories for versatile year-round usage
- Attachment frame for maximum versatility
- External fuel cap for easy refueling
- Pedal-operated hydrostatic transmission
- Easy-access controls for user comfort

Technical data

Engine manufacturer	Kawasaki
Engine name	FS Series V-Twin
Net power at preset rpm	9.6 kW @ 2900 rpm
Cylinder displacement	603 cm ³ / 36.8 cu.inch
Cylinders	2
Engine cooling	Air
Generator	15 A
Battery	12 V 24 Ah
Fuel Type	Gasoline
Fuel tank volume	12 lit / 3.2 gal.
Engine lubrication type	Full pressure
Oil filter	Yes
Transmission type	Hydrostatic
Transmission manufacturer	Tuff Torq
Transmission model	K46
Drive method	Pedal-operated
Speed forward, min-max	0-9 km/h / 0-5.6 mph
Speed reverse, min-max	0-9 km/h / 0-5.6 mph
Uncut circle	30 cm / 11.8 inch ¹
Cutting width, Min-Max	94-112 cm / 37-44.1 inch
Optional cutting decks	Combi 94, Combi 103, Combi 112
Cutting deck type	Combi
Cutting deck material	Steel
Cutting methods	BioClip®/Rear discharge
Cutting height, min-max	25 - 75 mm / 1 - 3 inch
Cutting height steps	9 pcs
Blade engagement	Automatic
Blades	3
Powder-coated cutting deck	Yes
Hour meter	Digital with pre-programmed service intervals
Seat material	Vinyl
Seat suspension	Yes
Seat back height	High
Foldable seat	Yes
Tyre dimensions, front	165/60-8
Tyre dimensions, rear	165/60-8
Wheelbase	88.7 cm / 34.9"
Ground clearance	105 mm / 4.13 inch
Base machine, length	202 cm / 79.5 inch
Base machine, width	89 cm / 35 inch
Base machine, height	115 cm / 45.3 inch
Weight	239 kg / 526.9 lbs
Sound pressure level at operators ear	83 dB(A)
Sound power level, guaranteed (LWA)	98 dB(A)

1) Measured on trim side turn

