



High-capacity garden tractor with side ejection ideal for large areas. Features a powerful design, first-class ergonomics and a two-cylinder Briggs & Stratton Endurance engine with full pressure lubrication. Pedal-operated hydrostatic transmission where direction and speed are controlled with pedals. The cruise control locks in the speed, for a comfortable drive.



TRIOCLIP
With the help of different accessories, our tractors can be converted to TrioClip, which means three different cutting systems in one machine: collection, BioClip® (mulching) and ejection.



HYDROSTATIC TRANSMISSION WITH LOCKING DIFFERENTIAL
Features a hydrostatic transmission that produces a smooth, variable forward and reverse speed and a pedal operated locking rear differential for increased traction while cutting on slopes or wet grass.



CRUISE CONTROL
A convenient, efficient function that ensures the tractor keeps an even speed, even if the lawn is undulating or sloping.



ELECTRIC ENGAGEMENT OF CUTTING BLADE/S
Easy engagement of cutting blade/s; simply pull the switch on the control panel.

Features

- Can be fitted with year-round accessories
- Step-through for easy mounting
- Easy-access cutting height adjustment
- Adjustable seat, while seated
- Armrests for improved comfort
- Ergonomic steering wheel

Technical data

Engine manufacturer	Briggs & Stratton
Engine name	Endurance Series V-Twin
Cylinder displacement	724 cm ³ / 44.2 cu.inch
Cylinders	2
Engine cooling	Air
Generator	16 A
Battery	12 V 28 Ah
Fuel Type	Gasoline
Fuel tank volume	15.1 lit / 4 gal.
Fuel tank location	Rear
Engine lubrication type	Pressure with Oilfilter
Oil filter	Yes
Transmission type	Hydrostatic
Transmission manufacturer	Tuff Torq
Drive method	Locking differential
Speed forward, min-max	0-8.4 km/h / 0-5.2 mph
Speed reverse, min-max	0-4.7 km/h / 0-2.9 mph
Cutting width	122 cm / 48 inch
Cutting deck type	Fabricated
Cutting deck material	Steel
Cutting methods	Side discharge
Cutting height, min-max	38 - 102 mm / 1.5 - 4 inch
Cutting height adjustment	Notch
Cutting height steps	6
Cutting height adjuster	Fender-mounted
Blade engagement	Electric
Blades	3
Blade type	Hi Performance
Anti-scalp wheels	2
Nose roller	Yes
Powder-coated cutting deck	Yes
Greasable mandrels	Yes
Deck Wash Port	Yes
Seat back height	High
Seat material	Nylon fabric
Steering wheel type	Ergonomic
Front-End Protection	Brush Guard Style Bumper
Hour meter	Digital with pre-programmed service intervals
Aluminum Racing Foot Pedal	Yes
Collector	Available as accessory
BioClip® kit/plate	Available as accessory
Tyre size, front	16x6.5-8"
Tyre size, rear	20x10-8"
Turning radius, min	41 cm / 16"
Base machine, width (chute down)	158.2 cm / 62.3 inch
Base machine, width (chute up)	123.7 cm / 48.7 inch

