



Lightweight straight shaft trimmer, perfect for homeowners. Easy starting with Smart Start® recoil system and fuel pump. Strong, braided wire cable drive. Comes with easy loading T25 semi automatic trimmer head.



**GRASS BEVEL GEAR**  
Bevel gear designed with high torque and the cutting equipment parallel to the ground for best cutting performance



**TAP 'N GO TRIMMER HEAD**  
Twin line cutting system with Tap 'n Go for quick line feed.



**FUEL PUMP**  
Fuel pump designed for easy starting.



**SMART START®**  
The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.

## Features

- Comfortable handle design
- Auto return stop switch for easy starting

## Technical data

|  |                                  |
|--|----------------------------------|
| Cylinder displacement                                    | 28 cm <sup>3</sup> / 1.7 cu.inch |
| Power output   | 0.8 kW                           |
| Maximum power speed                                      | 8000 rpm                         |
| Maximum recommended engine speed                         | 10000 rpm                        |
| Carburettor  | Zama                             |
| Fuel tank volume   | 0.4 lit / 13.53 fl oz            |
| Fuel consumption   | 507 g/kWh                        |
| Exhaust emissions (CO average)                           | 65.5 g/kWh                       |
| Equivalent vibration level (ahv, eq) front / rear handle | 4.8/6.4 m/s <sup>2</sup>         |
| Sound pressure level at operators ear                    | 97 dB(A)                         |
| Sound power level, guaranteed (LWA)                      | 114 dB(A)                        |
| Gear ratio   | 1:1.4                            |
| Drive gear angle   | 30°                              |
| OEM Trimmer head   | T25 (L)                          |
| OEM Grass blade  | –                                |
| OEM Saw blade  | –                                |
| OEM Harness  | –                                |
| Weight (excl. cutting equipment)                         | 4.8 kg / 10.6 lbs                |
| Tube length  | 1446 mm / 56.93 inch             |
| Tube diameter  | 25.4 mm / 1"                     |

